

SWIVEL PLATES

C-11B (6 pcs bead/粒珠)	C-11B / Flexible (6 pcs bead/粒珠)	C-11B (12 pcs bead/粒珠)	C-11C (6 pcs bead/粒珠)	C-22B (52 pcs bead/粒珠)	C-22B (15 pcs bead/粒珠)	C-22B / Flexible (15 pcs bead/粒珠)
						
ITEM NO. 品號 201110111	201110112	201110110	20111311	201220213	201220211	201220212
SIZE 規格 166 x 166 m/m	166 x 166 m/m	166 x 166 m/m	166 x 166 m/m	192 x 192 m/m	192 x 192 m/m	192 x 192 m/m
HEIGHT 高度 20 m/m	20 m/m	20 m/m	19 m/m	21 m/m	21 m/m	21 m/m
GAUGE 厚度 2.5 m/m	2.5 m/m	2.5 m/m	2.0 m/m	2.5 m/m	2.5 m/m	2.5 m/m
MATERIAL 材質 General Steel	General Steel	General Steel	General Steel	General Steel	General Steel	General Steel
PACKING 包裝 20 PCS/CTN 33.7 x 25.5 x 18 cm	20 PCS/CTN 33.7 x 25.5 x 18 cm	20 PCS/CTN 33.7 x 25.5 x 18 cm	20 PCS/CTN 35 x 23 x 19 cm	10 PCS/CTN 26 x 22 x 21 cm	10 PCS/CTN 26 x 22 x 21 cm	10 PCS/CTN 26 x 22 x 21 cm
WEIGHT 重量 N.W. 22.0 KGS G.W. 22.5 KGS	N.W. 22.0 KGS G.W. 22.5 KGS	N.W. 22.0 KGS G.W. 22.5 KGS	N.W. 18.3 KGS G.W. 18.8 KGS	N.W. 16.0 KGS G.W. 16.5 KGS	N.W. 15.0 KGS G.W. 15.8 KGS	N.W. 15.0 KGS G.W. 15.8 KGS
CUFT 材數 0.55	0.55	0.55	0.54	0.42	0.42	0.42

SWIVEL PLATES		LAZY SUSAN SWIVEL				
A-31C (Slope 3° - 15° rocker)	G-11	L-33 (25 pcs bead/粒珠)	L-44 (35 pcs bead/粒珠)	L-66 (66 pcs bead/粒珠)	L-88 (88 pcs bead/粒珠)	L-120 (136 pcs bead/粒珠)
						
ITEM NO. 品號 20131011	20111511	20133511	20144511	20166511	20188511	20120511
SIZE 規格 235 x 200 m/m	44 Dia m/m	76.5 x 76.5 (3"x3") m/m	99.3 x 99.3 (4"x4") m/m	153.3 x 153.3 (6"x6") m/m	208 (8") Dia m/m	304 (12") Dia m/m
HEIGHT 高度 82 x 72 m/m	15 m/m	9 m/m	9 m/m	9 m/m	9 m/m	9 m/m
GAUGE 厚度 2.5 m/m		0.8 m/m	2.5 m/m	2.5 m/m	2.5 m/m	2.5 m/m
MATERIAL 材質 General Steel	A.B.S	Zinc Steel	Zinc Steel	Zinc Steel	Zinc Steel	Zinc Steel
PACKING 包裝 10 PCS/CTN 45 x 41 x 22 cm	20 PCS/CTN 46.7 x 46.7 x 40 cm	200 PCS/CTN 32 x 25 x 18 cm	100 PCS/CTN 51 x 23 x 14 cm	50 PCS/CTN 34 x 25 x 19 cm	50 PCS/CTN 45 x 23 x 24 cm	20 PCS/CTN 32 x 21 x 32 cm
WEIGHT 重量 N.W. 26.0 KGS G.W. 27.0 KGS	N.W. 20.0 KGS G.W. 21.0 KGS	N.W. 19.0 KGS G.W. 20.0 KGS	N.W. 14.2 KGS G.W. 14.6 KGS	N.W. 11.8 KGS G.W. 12.3 KGS	N.W. 20.6 KGS G.W. 21.6 KGS	N.W. 14.0 KGS G.W. 15.0 KGS
CUFT 材數 1.43	3.44	0.51	0.58	0.57	0.88	0.76

STATIC LOAD TEST 荷重測試	MAX. LOAD (KGF) 最大荷重值(KGF)	REMARK 備註	TEST METHOD 測試方式
C-11B (6 pcs bead/粒珠)	900	No structure failure or loss of serviceability. 該轉盤於最大荷重值時，並無其結構或功能上之損壞。	- Secure the sample on the testing platform. - Apply the load on the sample top until it could not swivel or the approach of maximum load (900 kg). - Record the load and finding.
C-11B / Flexible (6 pcs bead/粒珠)	900	No structure failure or loss of serviceability. 該轉盤於最大荷重值時，並無其結構或功能上之損壞。	
C-11B (12 pcs bead/粒珠)	900	No structure failure or loss of serviceability. 該轉盤於最大荷重值時，並無其結構或功能上之損壞。	
C-11C (6 pcs bead/粒珠)	803	No structure failure or loss of serviceability. 該轉盤於最大荷重值時，並無其結構或功能上之損壞。	
C-22B (52 pcs bead/粒珠)	900	No structure failure or loss of serviceability. 該轉盤於最大荷重值時，並無其結構或功能上之損壞。	
C-22B (15 pcs bead/粒珠)	900	No structure failure or loss of serviceability. 該轉盤於最大荷重值時，並無其結構或功能上之損壞。	
C-11B / Flexible (15 pcs bead/粒珠)	900	No structure failure or loss of serviceability. 該轉盤於最大荷重值時，並無其結構或功能上之損壞。	- 確保該轉盤置於測試台上。 - 將重量置於該轉盤上，直到無法轉動，或其達至最大荷重值900公斤。 - 記錄該轉盤之荷重及測試結果。
A-31C (Slope 3° - 15° rocker)	N/A	N/A	
G-11	N/A	N/A	
L-33 (25 pcs bead/粒珠)	280	The swivel plate still can be swivel during test. 測試時轉盤可正常轉動。	
L-44 (35 pcs bead/粒珠)	300	The swivel plate still can be swivel during test. 測試時轉盤可正常轉動。	
L-66 (66 pcs bead/粒珠)	680	The swivel plate still can be swivel during test. 測試時轉盤可正常轉動。	
L-88 (88 pcs bead/粒珠)	780	The swivel plate still can be swivel during test. 測試時轉盤可正常轉動。	Secure the sample on the test platforms. Place a load of 10 kg on the sample each time until the sample can't be swiveled. Record the Max. load that the sample still can't be swiveled. 確保轉盤於測試台上。每次增加10公斤於轉盤上，直到該轉盤無法轉動為止。當轉盤之乘載荷重達至該記錄最大值時，則無法轉動。
L-120 (136 pcs bead/粒珠)	810	The swivel plate still can be swivel during test. 測試時轉盤可正常轉動。	